



# Bluetank

Polyethylene tanks for DEF storage and delivery



## Description

High - density linear polyethylene tanks, monolithic, with high mechanical, chemical and UV resistance. Available in azure color (basic line) and in white color (higher chemical resistance version).

- Available volumes: 2.000 L, 3.000 L, 5.000 L, 7.500 L and 10.000 L.
- Manhole with threaded lid, diameter 42 cm for 2.000 L, 3.000 L and 5.000 L tanks and 55 cm for 7.500 L and 10.000 L tanks.
- 1" vent device.
- 2" loading plug.
- 1" suction pipe.

## Outfittings

- Lockable steel cabinet.
- Self-priming diaphragm electropump, 230 V - 50 Hz, flow rate 30 L/min.
- Digital fuel meter.
- EPDM flexible hose, size 3/4", length 6 m.
- Automatic dispensing nozzle.

## Accessories



### Retention Basin for Bluetank

Retention basin, 100% tank's volume capacity, made in carbon steel

## Technical data

Model	Nominal capacity (lt)	Highness (mm)	Length (mm)	Diameter (mm)	Ø Manhole cover (mm)	Vfiato	Basin 100%		
							Length (mm)	Width (mm)	Highness (mm)
BLUETANK2000	2,000	1,380	1,700	1,300	200	Si	2,350	1,500	600
BLUETANK3000	3,000	1,530	2,000	1,450	400	YES	2,400	1,800	700
BLUETANK5000	5,000	1,780	2,470	1,700	400	Si	3,200	1,900	890
BLUETANK7500	7,150	2,010	3,180	1,890	550	YES	3,850	2,100	950
BLUETANK10000	10,400	2,370	3,100	2,250	550	Si	4,200	2,400	1,000

## Product code

PLTORZ	X	X	X
<b>Model</b> PLTORZ = Bluetank	<b>Volume</b> 2000 = 2000 l 3000 = 3000 l 5000 = 5000 l 6000 = 6000 l 10000 = 10000 l	<b>Version</b> AdBlue = High chemical resistance L = Basic	<b>Typology</b> /BOX = Box

Not all combinations are available