Carrytank® 220 Pick-up

Polyethylene tank for Diesel fuel transport on pick-up vehicles, in exemption from ADR

NEW

Pick-up wheel-arch fit

Mechanical level indicator

Battery connection

Gasoline version available

Description

The CARRYTANK 220 pick-up, an evolution of our CARRYTANK 220, is a transportable diesel fuel tank made from roto-molded linear polyethylene. The 220 pickup tank can be placed inside the body of a pickup vehicle and remain below the height of the side boards, allowing the installation of the most common closures for bodies. Due to this it's sheltered from atmospheric agents such as sun, rain or snow giving product a longer life. Drawing on its considerable experience, ES has also optimized the dimensions of the tank for international transport.
Also available in gasoline version. Homologated diesel version is also available.

Main features

- made from roto-molded linear polyethylene
- reinforced padlockable lid and reinforced closures.
- level indicator for fitting the most common filtering systems
- aluminum filling plug
- safety valve
- transfer unit
- forklift pockets for lifting
- handles for lifting when empty
- recesses for securing straps to the support base
- drip-proof nozzle holder for improved cleanliness and protection
- all inserts are made of aluminum or diesel fuel-compatible material.

Outfittings

Configuration model AC:

- DC fuel transfer pump, mod. DEVIL40 (12 or 24 V), flow rate 40 l/min.
- 4 m of hose.
- Automatic nozzle.
- For the exempted version: 6 metres of electric cable and clamps for battery connection.
- For the homologated version: 6 metres of electric cable and bipolar connector for battery connection.
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

Configuration model BC:

- AC fuel transfer pump, mod. DEVIL55 (230 V), flow rate 55 l/min.
- 4 m of hose.
- Automatic nozzle.
- 2 m of power cable with Schuko plug for connection to BC supply (Diesel fuel).
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

Configuration model ZC:

- DC fuel transfer pump, mod. 12/24V, flow rate 35/70 l/min
- 4 m of hose.
- Automatic nozzle.
- For the exempted version: 6 metres of electric cable and clamps for battery connection.
- For the homologated version: 6 metres of electric cable and bipolar connector for battery connection.
- Optional: digital flow meter, mod. M24.
- Optional: water separator filter.

Accessories

Emil Level

Remote control system for monitoring the fuel level in the tank

Drip Tray

Filter Water captor 70

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 30µm. Flow rate 70 l/min.

ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.

Digital fuel meter, mod. M24, for Diesel Fuel

Technical data

Model	Nominal capacity (lt)	Width (mm)	Base width (mm)	Depth (mm)	Base depth (mm)	Highness (mm)	Thickness (mm)	Empty weight (kg)	Weight with pump unit (kg)
CTPG220	220	1,155	1,050	805	720	450	7	19	31

Loading Plan

Model	Container 20'	Container 40'	Container 40' HC	Std truck 2700h mm
CTPG220	70	140	168	192

Product code

CTP	X	X	X	X
Model **CTP** = Carrytank pickup	**Fuel** **G** = Diesel **K** = Diesel homologated	**Volume** **220** = 220 l	**Pump** **A** = 40 l/min **B** = 55 l/min **Z** = 40 l/min dual voltage 12/24V	**Nozzle** **C** = Automatic 60 l/min

Not all combinations are available

Approval

ADR approved

RID ADN IMDG approved

Transportable materials	Diesel / UNI1202
Clases ADR	3
Packaging group	II - III