



DK 200

High flow rate portable dispenser unit.



Handy Kit (optional)



Handy Kit (optional)



Fuel meter (optional)



Pistola di erogazione ad alta portata (optional)

Description

High flow rate portable dispenser unit. DK 200 dispenses Diesel fuel at a rate of up to 200 L/min and controls the flow with great precision ($\pm 1\%$) thanks to the oval-gear flow meter (on request). The low weight of the unit and the possibility of fixing wheels make it easy to handle and suitable for operating on worksites where vehicles with large storage tanks are required. The unit features a sturdy steel frame.

Main features

- Flow rate up to 200 L/min.
- Inlet/Outlet: coupling 1" 1/2 BSP.
- Continuous AC operation, 230 V - 50 Hz.
- On/Off switch.
- Electrical cable, 6 m length.
- Noise level below 75 dB.

Accessories

- Handy Kit: wheels and handle (Cod. DK200YHWKIT).
- Fuel Meter: model K700, oval gear type, flow rate up to 220 L/min, accuracy: +/- 1%. (Cod. CTLK700).
- Hose kit, size 1" 1/2, complete with rubber hose 10 m + camlock coupling. (Cod. TUB112MT10GASRACCAM).
- High flow nozzle, flow rate up to 280 L/min with swivel. (Cod. PISTAUTA280).