Emilcaddy® 55-110

Polyethylene mobile tanks for fuel with wheels



Handle for handling and lifting

Nozzle holder

Safety valve with swivel joint

Puncture-proof wheels

Description

Tanks made in roto-molded linear polyethylene, ideal for the refueling of small and light operating vehicles or crafts. The tank has the following approvals: ADR (road transport), ADN (transport on inland waters), IMDG (sea transport) and RID (rail transport).
Gasoline version is also available.
AdBlue/DEF version is also available.
Featuring a unique design with ergonomic grip for excellent handling and lifting, Emilcaddy is equipped with puncture proof wheels designed to be driven on any surface. In addition to lightness and handiness, the structure, devoid of sharp edges, and the reinforcement ribs confer great strength and resistance. Emilcaddy can be filled either horizontally or vertically with the same amount of fuel. The tank is equipped with a filling plug with integrated air vent device and a safety ball valve set up on the suction/drain point. Emilcaddy line, thanks to its features, represents an optimal and safe solution for refueling operations both in professional fields and in sport or leisure activities.

Main features

- Top handle for easy gripping and lifting.
- Integrated recesses for securing with ratchet lashing straps.
- Suction/drain safety ball valve.
- Filling plug with integrated non-spill vent.
- Lower handle for manual lifting operations.
- Puncture proof wheels and foot support.
- Front nozzle holder.
- Manual and electric pump support

Outfittings

Emilcaddy® for DIESEL fuel (Yellow version), available with:

Configuration model MA:

- Manual rotary vane pump made in aluminum
- Manual nozzle
- 3 m of fuel hose

Configuration model AA and AC:

- 12 V or 24 V electric pump, flow rate 40 L/ min
- Manual or automatic nozzle
- 3 mt hose.
- 5 mt of battery power cable and clamps for battery connection.

Accessories

Digital fuel meter, mod. M24, for Diesel Fuel

Strainer filter stainless steel

For diesel and gasoline. Impurity filtration. Filter capacity 60µm. Flow rate 50 l/min.

ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.

Folding Tray

Portable flexible spill containment tray

Lead-acid battery with battery charger (European plug type C)

Manganese 12V or 24V battery with battery charger (European plug type C) and battery slot

Manganese 12V or 24V battery with battery charger (cigarette lighter plug) and battery slot

Technical data

Model	Nominal capacity (lt)	Width (mm)	Depth (mm)	Highness (mm)	Empty weight (kg)	Empty weight, approved gasoline version (kg)
EMG55	55	460	360	900	8	9
EMG110	110	460	440	1,100	12	13

Loading Plan

Model	Container 20'	Container 40'	Container 40' HC	Std truck 2700h mm
EMG55	72	176	176	208
EMG110	72	176	176	208

Product code

Emilcaddy 55-110

EM	X	X	X	X
Model **EM** = Emilcaddy	**Fuel** **G** = Diesel **K** = Diesel homologated	**Volume** **55** = 55 l **110** = 110 l	**Pump** **M** = Rotary **A** = 40 l/min	**Nozzle** **A** = Diesel manual **C** = Automatic 60 l/min

Not all combinations are available

Approval

Transportable materials	Diesel / UNI1202 Gasoline / UNI1203 Ethanol / UNI1170*
Clases ADR	3
Packaging group	II - III