GIANTank

Polyethylene tank for fuel delivery and storage

Leak detector

Filling quick cap 2"

Lockable lid

Gas struts for lid

Description

NOT AVAILABLE FOR THE ITALIAN MARKET

GIANTank® is the innovative solution by Emiliana Serbatoi for the storage and delivery of diesel fuel designed and realized in order to respect technical and environmental strict rules. GIANTank® combines robustness of the material and environmental protection thanks to a secondary containment designed to hold 110% of the volume of the tank, that has a capacity of 3.300 liters. The tank is manufactured in linear polyethylene with rotational molding that provides the product with compactness and sturdiness, in addition to a particularly innovative and ergonomic design. GIANTank® is equipped with a padlocked reinforced lid (with gas stoppers, in order to facilitate closing and opening operations, and lockable hinges); the lid covers and protects the fuel compartment which houses a complete transfer unit with electric panel, electric pump, fuel meter, automatic nozzle, level indicator, loading port, safety valves and delivery hose (combined, as an option, with up to 15 meters hose pipe with reel). GIANTank® is projected to be lifted empty thanks to the special forklift pockets, for easily-moved operations, located on the bottom of the tank. All GIANTank® inserts are made of aluminum for Diesel fuel-compatible material. AdBlue®/DEF version is also available: for information please refer to AdBlue®/DEF section. On request, the version for lubricants is available too.

Main features

- Secondary containment designed to hold 110% of the volume of the tank.
- Electric switchboard.
- Minimum level pump block.
- Leak detector.
- Filling quick cap 2".
- Air vent 1"1/2 with flame arrestor mesh.
- Overfill prevention valve calibrated to interrupt thefuel flow at 90% of the tank's volume

Outfittings

CONFIGURATION GE:

- GE Version for generating sets feeding (without pump).
- Mechanical flow meter.
- Mechanical level gauge.
- Quick couplings 3/4".

CONFIGURATION BC:

- Electric pump mod. Devil 55, flow rate 55 l/min.
- 6 m refueling hose.
- Mechanical flow meter.
- Automatic nozzle mod. A60.
- Mechanical level gauge.
- Electric switchboard

CONFIGURATION GF:

- Electric pump mod. Devil 70, flow rate 70 l/min.
- 6 m refueling hose.
- Mechanical flow meter.
- Automatic nozzle mod. A80.
- Mechanical level gauge.
- Electric switchboard

CONFIGURATION LF:

- Electric pump flow rate 80 l/min.
- 6 m refueling hose.
- Mechanical flow meter.
- Automatic nozzle mod. A80.
- Mechanical level gauge.
- Electric switchboard

CONFIGURATION DC:

- Electric pump mod. DPUMP 12V, flow rate 60 l/min.
- 6 m refueling hose.
- Mechanical flow meter.
- Automatic nozzle mod. A80.
- Mechanical level gauge

Accessories

Rapid couplings

Filter Water captor 70

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 30µm. Flow rate 70 l/min.

ES Filter

For diesel and gasoline. Water absorption and impurity filtration. Filter capacity 10µm. Flow rate 70 l/min.

Hose reel

Fuel handling and delivery equipment.

OCIO

Tank level indicator

Emilprobe®

Alarm system that continuously monitors, in text and graphic form, the liquid in the tank (actual volume, level, temperature and the presence of water)

Emil Level

Remote control system for monitoring the fuel level in the tank

Technical data

Model	Nominal capacity (lt)	Width (mm)	Depth (mm)	Highness (mm)	Weight with pump unit (kg)
GT33	3,300	1,125	2,350	1,800	320

Product code

GT	X	X	X	X
Model **GT** = Giantank	**Fuel** **G** = Diesel	**Volume** **3300** = 3300 l	**Pump** **(vuoto)** = GE version **B** = 55 l/min **D** = 60 l/min	**Nozzle** **C** = Automatic 60 l/min **F** = Automatic 80 l/min

Not all combinations are available