




Hippotank® for AdBlue®

Portable tanks made in polyethylene for transport and delivery of DEF.



Description

Portable tanks made in polyethylene for transport and delivery of DEF. Hippotank® is manufactured in rotomolded linear polyethylene, a material that ensures excellent resistance against shocks, temperature changes, chemical agents and bad climate conditions.

Main features

- Its transparency also allows a constant sight monitoring of the fluid level.
- Side pockets, reinforced by zinc-coated carbon steel profiles, allow lifting from bottom by means of forklift (full load).
- 220 mm diameter top hatch with lockable screw lid, gasket, loading port with built-in air vent device and lockable security bar.
- 12 V or 24 V DC diaphragm battery pump, flow rate 30 L/min complete with cable and clamps for battery connection; the fluid transfer unit is fixed in a proper housing inside the tank and provided with a lockable door.
- EPDM hose, 5 m long, equipped with automatic nozzle.

Outfittings

- 12 V or 24 V DC diaphragm battery pump, flow rate 30 L/min
- Cable and clamps for battery connection
- EPDM hose, 5 m long
- Automatic nozzle.

Accessories



Manganese 12V battery with battery charger (European plug type C) and battery slot



Manganese 12V battery with battery charger (cigarette lighter plug) and battery slot



Digital flow meter for AdBlue K24

Technical data

Model	Nominal capacity (lt)	Width (mm)	Depth (mm)	Highness (mm)	Empty weight (kg)	Weight with pump unit (kg)
HTKA980	960	995	1,830	1,000	95	105

Product code

HT	X	X	X	X
Model HT = Hippotank	Fuel A = AdBlue	Volume 980 = 980 l	Pump S = Battery 12/24v AdBlue	Nozzle H = Automatic AdBlue