




Insulated Container

Box containers for phyto-pharmaceuticals, pesticides and other products for agriculture use and for external use



Description

Safety cabinets for phyto-pharmaceuticals, pesticides and other products for agriculture use. Designed to meet all the latest requirements relating to the safe storage and disposal of hazardous products. Rugged galvanized steel frame, panelised with self-extinguishing insulating "sandwich" panels. Customised dimensions available on request.

Main features

- Flat roof made of self-extinguishing insulating "sandwich" panels, thickness 30+30 mm. The insulating mass consists of a rigid plastic with a high level of insulating power, made from polyurethane resins (PUR) and poliisocianurates (PIR) both self-extinguishable, with a thermal conductivity at 10°C: K= 0.020 W/mK.
- Hinged lockable double door.
- Basement frame made of steel profiles, thickness 15/10 mm.
- Hot-dip galvanised sump containment, steel thickness 30/10 mm, height 18 cm.
- Floor made with removeable hot-dip galvanised steel grates, dim. 7x252x20/10 mm, load capacity 500 Kg/mq.
- Drain pipe for cleaning and drainage operations.
- N. 2 air grills for ventilation, dim. 15x25 cm, one set on the door and one on the opposite side.
- Safety sign indicating the presence of hazardous, toxic and corrosive products.

Accessories

- ELECTRICAL SYSTEM:
 - Standard: according to the European standards in force; electrical materials are complies with IMQ standards.
 - Voltage: 230 V - 50 Hz.
 - Inlet connection: sealed box mounted on the outer wall of the container.
 - Electric fuse box, made of self-extinguishing PVC; main differential thermo-magnetic two poles circuit breaker, 16 A rating, differential current 0,03 A.
 - N. 1 ceiling lamp complete with 1x60 W incandescent lamp.
 - N. 1 wall mounted power outlet, 10 amp rating.
- ELECTRICAL HEATER, 1.500 W, cod. CNTCOIYCONVETTORE

Technical data

Model	External depth (mm)	External width (mm)	External height (mm)	Internal depth (mm)	Internal width (mm)	Internal height (mm)	Tub capacity (lt)	Flow rate (kg/mq)	Electrical system
CNTCOI24X15	1,500	2,400	2,400	1,380	2,280	2,000	645	500	Non incluso
CNTCOI24X15EL	1,500	2,400	2,400	1,380	2,280	2,000	645	500	Incluso
CNTCOI40X24	2,400	4,100	2,400	2,250	3,960	2,000	1,725	500	Non Incluso
CNTCOI40X24EL	2,400	4,100	2,400	2,250	3,960	2,000	1,725	500	Incluso

Customised dimensions available on request