



## Speedy tank

Trailer suitable for rapid connection of transportable fuel tanks. Certified flatbed trailer for road transport of fuel.



### Description

Speedy Tank consists of a flatbed trailer with side boards, suitable for road goods transport, equipped for quick connection with our transportable tanks in accordance with the ADR regulation.

## Main features

- "Twin-frame" system. Axles with rubber suspension. Steel galvanised frame. Rigid A-frame connecting the coupling system and the axles (direct linkage EEC 94/20). Assisted tilting.
- GKN braking system.
- Independent modular flatbed: modular and thick-edged profiles - welded modular crossbeams - square tubular corner pieces.
- Side boards: 350 mm high. The front and back boards can be opened. Boards close with spring hooks. Galvanised steel ribbed sheeting.
- Approved coupling.
- Towing eyelet (available on request), cod. RIMYGANCIOULPIO.
- Axles: hot-galvanised steel - non-cutting edges with bars for fitting.
- Lights: compact single-block, built-in and protected on the rear beam.
- Flatbed: made of plywood Hi-grip phenolic resin coated.

## Outfittings

1. Speedy Tank RIMSPEEDY1 (suitable for tank mod. TRASPO® TFT250 and TFT330 INOX).
2. Speedy Tank RIMSPEEDY2 (suitable for tank mod. TRASPO® TFT380, TFT450 and TFT620).
3. Speedy Tank RIMSPEEDY3 (suitable for tank mod. TRASPO® TFT910).
4. Speedy Tank RIMSPEEDY4 (suitable for tank mod. EMILCUBE®, TANKUBE and HIPPO TANK®).

## Technical data

Model	Total mass (kg)	Payload (kg)	Floor size (mm)	Total dimensions (mm)	Brake system	Number of wheels/axles
RIMSPEEDY1	900	720	1800x1450	2750x1510	Si	2/1
RIMSPEEDY2	900	700	2080x1450	3090x1560	Si	2/1
RIMSPEEDY3	1,500	1,120	3060x1750	4440x1810	Si	4/1
RIMSPEEDY4	2,500	2,120	3060x1750	4440x1810	Si	4/1